CX Bulldog Nock Collar Fitment Outlined in Red Below

ARROW SPECS					PREMIUM INSERT		BULLDOG NOCK COLLAR		LAUNCHPAD PRECISION NOCK	
ARROW	SPINE	GPI	ID	OD	INSERT #	12PK PART #	COLLAR #	12PK PART #	NOCK	12PK PART #
PHOTON 4MM	400	7.7	0.166	0.228	#1 - 4MM Outsert 50GR	CX0740	#1 - 4MM Black	CX0760	4MM Pearl White	CX0750
	350	8.2	0.166	0.232	#1 - 4MM Outsert 50GR	CX0740	#1 - 4MM Black	CX0760	4MM Pearl White	CX0750
	300	8.9	0.166	0.237	#2 - 4MM Outsert 50GR	CX0741	#1 - 4MM Black	CX0760	4MM Pearl White	CX0750
MAXIMA RED 4MM	400	9.3	0.166	0.240	#2 - 4MM Outsert 50GR	CX0741	#2 - 4MM Black	CX0761	4MM Pearl White	CX0750
	350	10.2	0.166	0.246	#3 - 4MM Outsert 50GR	CX0742	#2 - 4MM Black	CX0761	4MM Pearl White	CX0750
	300	11.3	0.166	0.254	#3 - 4MM Outsert 50GR	CX0742	#3 - 4MM Black	CX0762	4MM Pearl White	CX0750
PREDATOR AIR 4MM	400	8.8	0.166	0.237	#2 - 4MM Outsert 50GR	CX0741	#1 - 4MM Black	CX0760	4MM Pearl White	CX0750
	350	9.8	0.166	0.243	#2 - 4MM Outsert 50GR	CX0741	#2 - 4MM Black	CX0761	4MM Pearl White	CX0750
	300	10.7	0.166	0.249	#3 - 4MM Outsert 50GR	CX0742	#3 - 4MM Black	CX0762	4MM Pearl White	CX0750